

Range of INDUSTRIAL batteries

6 VOLT DEEP CYCLE US BATTERIES

Part No	Cross Ref	Ah/20hr	Length mm	Width mm	Height mm	Terminal	Weight kgs
US 1800	T605	208	260	181	286	UTL	25.4
US 2000	T6220	216	260	181	286	UTL	26.7
US 2200	T105	232	260	181	286	UTL	28.5
US2200DT	T105	232	260	181	286	DUAL	28.5
US125	T125	242	260	181	286	UTL	30.4
US125DT	T125	242	260	181	286	DUAL	30.4
US145	T145	251	260	181	302	DUAL	31.8
US250	J250P	258	295	181	295	DUAL	32.7
US250HC	N/A	283	295	181	295	DUAL	35.4
US305	J305P	305	302	181	371	DUAL	39.5
US305HC	J305H	335	302	181	371	DUAL	43.6
USL16	L16P	375	302	181	425	DUAL	51
USL16HC	L16H	415	302	181	425	DUAL	53

8 VOLT DEEP CYCLE US BATTERIES

Part No	Cross Ref	Ah/20hr	Length mm	Width mm	Height mm	Terminal	Weight kgs
US8VGC	T875	170	260	181	286	DUAL	29.5
US8VGCCHC	T875	183	260	181	286	DUAL	30.5

12 VOLT DEEP CYCLE US BATTERIES

Part No	Cross Ref	Ah/20hr	Length mm	Width mm	Height mm	Terminal	Weight kgs
US185	J185P	195	397	179	378	DUAL	49.5
US185HC	J185H	215	397	179	378	DUAL	54.4
US24TM	24TMX	85	273	171	248	DUAL	21.8
US27TM	27TMX	105	324	171	248	DUAL	24.5
US27TMX	27TMH	120	324	171	248	DUAL	24.5
US31TMX	30/31XHS	130	349	171	248	DUAL	29.9
EV145	J150	145	346	171	311	DUAL	39.5

ODYSSEY BATTERIES

Part No	Volt	Ah/20hr	CCA (-18°C)	MCA (0°C)	Dimensions L x W x H	Weight kgs	Terminals	Layout
PC310	12	8	100	155	137 x 86 x 101	2.7	M4 bolt	2
PC535	12	14.8	200	265	170 x 99 x 155	5.4	M6 bolt	0
PC545	12	14	170	240	178 x 86 x 132	5.7	M6 bolt	0
PC625	12	18	265	350	170 x 99 x 175	6.0	M6 stud	0
PC680	12	17	220	300	185 x 79 x 170	7.0	M6 bolt	0
PC925T	12	28	380	500	169 x 179 x 128	11.8	M6 bolt	0
PC1200T	12	44	550	725	200 x 170 x 173	17.4	M6 bolt	0
PC1500DT	12	68	825	1050	276 x 178 x 199	24.0	DUAL	1
PC1700T	12	68	875	1175	331 x 168 x 176	27.6	M6 bolt	0
PC2150T	12	100	1090	1370	330 x 173 x 239	34.1	9.5 stud	2
PC2250T	12	126	1225	1550	286 x 269 x 208	39.0	DUAL	0

OPTIMA BATTERIES

Part No	Volt	Ah/20hr	CCA (EN)	RC Mins	Dimensions L x W x H	Weight kgs	Terminals	Layout
RTS2.1	6	50	815	104	253 x 90 x 200	8.3	1	2
RTS3.7	12	44	730	90	237 x 172 x 194	15.0	1 and side	2
RTS4.2	12	50	815	104	256 x 174 x 200	17.6	1 and side	2
YTS2.7	12	41	510	70	234 x 127 x 227	11.6	1 or 3	0
YTS4.2	12	55	690	120	254 x 174 x 200	19.9	1 and side	2
YTS5.5	12	75	975	155	324 x 166 x 238	27.1	1	2

Battery Solutions York Ltd

75 Leeman Road, YO26 4XH - Telephone: 01904 626414 - Fax: 01904 652469